

AC FLUORESCENT BLAZE ORANGE. 6 X 312GM

Version 1.1

Print Date 10/02/2006

REVISION DATE: 08/29/2006

SECTION 1 - PRODUCT IDENTIFICATION / PREPARATION INFORMATION**Product Information**

Trade name : AC FLUORESCENT BLAZE ORANGE. 6 X 312GM
Product code : 49011F 522

Supplier : Tremco Canada division
220 Wicksteed Avenue
Toronto, ON M4H 1G7

Telephone : (416) 421-3300
Emergency Phone: : (613) 996-6666

Product use : Coating

Preparation Information

Prepared by: : Sewnauth Raghunandan
Date: : 08/29/2006
Telephone : (416) 421-3300

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

Orange. Aerosol. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system.
Eyes : Vapor and/or mist may cause eye irritation. Direct contact may cause temporary redness and discomfort.
Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.
Skin : May cause mild irritation.

Aggravated Medical Conditions

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Propellants in product, such as propane and isobutane, are asphyxiants and can be anesthetic at high concentrations. Repeated overexposure to vapors and/or material may injure the liver, kidneys and respiratory system unless suitable engineering controls and/or personal protective equipment are used. Prolonged or repeated exposure to xylene may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, heart muscle sensitization and arrhythmia, hearing loss, and brain, liver, kidney damage. Xylene overexposure may affect fetal development. Prolonged or repeated overexposure to acetone may cause liver damage, Central Nervous System depression and narcosis. The International Agency for Research on Cancer (IARC) has evaluated ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in

AC FLUORESCENT BLAZE ORANGE. 6 X 312GM

Version 1.1

Print Date 10/02/2006

REVISION DATE: 08/29/2006

exposed humans. Propellants in product, such as propane and isobutane, are asphyxiants and can be anesthetic at high concentrations.

Target Organs: Eyes., Skin.

SECTION 3 : HAZARDOUS INGREDIENTS

Chemical Name	CAS-No.	Weight % Range
---------------	---------	----------------

		> 60.0
Liquefied petroleum gases	68476-86-8	15.0 - 40.0
Isobutane	75-28-5	7.0 - 13.0
Acetone	67-64-1	7.0 - 13.0
Xylene	1330-20-7	1.0 - 5.0
Ethylbenzene	100-41-4	0.1 - 1.0

The ingredients listed above are hazardous as defined in the controlled products regulation. (CPR).

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation	:	Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.
Eye contact	:	Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
Skin contact	:	Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5: FIRE / EXPLOSION HAZARDS

Flash point	:	Not available.
Method	:	Flame Extension
Burning rate	:	Flame Extension 45cm+
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	If water fog is ineffective, use carbon dioxide, dry chemical or foam.
Hazardous combustion products	:	Carbon monoxide and carbon dioxide can form. Smoke, fumes. Oxides of cobalt. Oxides of barium. Oxides of zirconium. Oxides of titanium. Oxides of boron.
Protective equipment for firefighters	:	Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water may be used to cool containers to minimize pressure build-up.

AC FLUORESCENT BLAZE ORANGE. 6 X 312GM

Version 1.1

Print Date 10/02/2006

REVISION DATE: 08/29/2006

Fire and explosion conditions : Extremely flammable vapors. Closed container, may burst when exposed to extreme heat. Vapor concentrations in enclosed areas may ignite explosively. Empty containers may contain ignitable vapors. Vapors may travel to sources of ignition and flashback. Contents under pressure. Do not puncture or incinerate. Do not expose to heat or store at temperatures above 100°F/38°C.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not smoke, weld, generate sparks, or use flame near container. Keep away from heat and flame. Store below 100 F/38C. Do not store in direct sunlight. Do not puncture or incinerate aerosol containers, even when empty. Do not freeze. Store under dry warehouse conditions away from heat and all ignition sources.

SECTION 8 - PREVENTIVE MEASURES/EXPOSURE CONTROLS/PERSONAL PROTECTION**Personal protection equipment**

Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.

Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.

Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.

Skin and body protection : Typical full cover clothing.

Protective measures : Use professional judgment in the selection, care, and use.

Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use general ventilation and/ or local exhaust to reduce the airborne contaminant concentration below the exposure limit listed in the MSDS

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Isobutane	75-28-5	ACGIH TWA: Ontario TWA:	1,000 ppm 1,900 mg/m3	
Acetone	67-64-1	Ontario TWA: Ontario STEL: ACGIH TWA: ACGIH STEL:	500 ppm 750 ppm 500 ppm 750 ppm	

AC FLUORESCENT BLAZE ORANGE. 6 X 312GM

Version 1.1

Print Date 10/02/2006

REVISION DATE: 08/29/2006

Chemical Name	CAS Number	Regulation	Limit	Form
Xylene	1330-20-7	Ontario TWA: Ontario STEL: ACGIH TWA: ACGIH STEL:	435 mg/m3 650 mg/m3 100 ppm 150 ppm	
Ethylbenzene	100-41-4	Ontario TWA: Ontario STEL: ACGIH TWA: ACGIH STEL:	435 mg/m3 540 mg/m3 100 ppm 125 ppm	

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State	: Liquid
Form	: Aerosol
Color	: Orange
Odor	: Solvent
pH	: Not available.
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: Not available.
Water solubility	: Negligible
Evaporation Rate:	: Not available.
Specific Gravity	: 1.09
% Volatile Weight	: 35 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid	: Oxidizing agents.
---------------------	---------------------

SECTION 11 - TOXICOLOGICAL INFORMATION

, CAS-No.:	
Acute oral toxicity (LD-50 oral)	3,500.00 mg/kg
Xylene, CAS-No.: 1330-20-7	
Acute oral toxicity (LD-50 oral)	3,523 - 8,600 mg/kg (Rat)
Acute inhalation toxicity (LC-50)	6,350 mg/l (Rat)
Ethylbenzene, CAS-No.: 100-41-4	
Acute oral toxicity (LD-50 oral)	3,500 mg/kg (Rat)
Acute dermal toxicity (LD-50 dermal)	17,800 mg/kg (Rabbit)



AC FLUORESCENT BLAZE ORANGE. 6 X 312GM

Version 1.1

Print Date 10/02/2006

REVISION DATE: 08/29/2006

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Disposal Method : Dispose according to all applicable regulations (hazardous household waste depot, or as liquid industrial waste for industrial product)., Recycle or dispose of in compliance with local, provincial and federal regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

TDG / DOT Shipping Description:
LIMITED QUANTITY

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

Canadian Regulations:

WHMIS Classification : A, B5, D2A, D2B
This is a "controlled product" under the Canadian Workplace Hazardous Materials Information System (WHMIS).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Other Regulations:

Regulatory VOC (less water and exempt solvent) : 386 g/l

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	3
Flammability	4
Reactivity	0
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

Further information:

Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to his own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

AC FLUORESCENT BLAZE ORANGE. 6 X 312GM

Version 1.1

Print Date 10/02/2006

REVISION DATE: 08/29/2006

Prepared by: Sewnauth Raghunandan

Legend

ACGIH - American Conference of Governmental Hygienists	OSHA - Occupational Safety and Health Administration
DOT - Department of Transportation	PEL - Permissible Exposure Limit
DSL - Domestic Substance List	RCRA - Resource Conservation and Recovery Act
EPA - Environmental Protection Agency	STEL - Short Term Exposure Limit
HMIS - Hazardous Materials Information System	TLV - Threshold Limit Value
IARC - International Agency for Research on Cancer	TSCA - Toxic Substances Control Act
MSHA - Mine Safety Health Administration	TWA - Time Weighted Average
NDSL - Non-Domestic Substance List	V - Volume
NIOSH - National Institute for Occupational Safety and Health	VOC - Volatile Organic Compound
NTP - National Toxicology Program	WHMIS - Workplace Hazardous Materials Information System